

**CAMSHAFT: Performer RPM Roller Hydraulic
CATALOG #2263 & 2264**



**ENGINE: 1967 & Later Chevrolet 500+ c.i.d. V8
RPM RANGE: 1500-6500**

CAUTION: Do not use dual valve springs. Use recommended valve springs with closed pressure of 175 lbs., open pressure of 465 lbs, and max lift of .700". Use stock ratio rockers only.

Duration at .006" Lift:	Intake 308°	Exhaust 315°
Duration at .050" Lift:	Intake 248°	Exhaust 256°
Lift at cam:	Intake .371"	Exhaust .381"
Lift at valve:	Intake .632"	Exhaust .648"
Timing at .050 Lift: Open	Close	
Intake	14.5° BTDC	62.5° ABDC
Exhaust	53.5° BBDC	13.5° ATDC
Centerlines:	Int. 109.5° ATDC	Exh. 114.5° BTDC
Lobe Separation:	112°	

CAUTION: Use Edelbrock Performer-Link Timing Chain and Gear Set #7810 or Accu-Drive gear drive #7891. Do not use late model timing chain and gear sets that are designed for emission-controlled engines. These timing sets are machined in a retarded position and are not recommended for this camshaft installation. Edelbrock Timing Sets feature three keyways for specified timing selection. Use "0" position for most applications.

Catalog #2263, 2264
Rev. 5/15/13 - QT/mc

©2013 Edelbrock LLC
Brochure #63-2263C

**CAMSHAFT: Performer RPM Roller Hydraulic
CATALOG #2263 & 2264**



**ENGINE: 1967 & Later Chevrolet 500+ c.i.d. V8
RPM RANGE: 1500-6500**

CAUTION: Do not use dual valve springs. Use recommended valve springs with closed pressure of 175 lbs., open pressure of 465 lbs, and max lift of .700". Use stock ratio rockers only.

Duration at .006" Lift:	Intake 308°	Exhaust 315°
Duration at .050" Lift:	Intake 248°	Exhaust 256°
Lift at cam:	Intake .371"	Exhaust .381"
Lift at valve:	Intake .632"	Exhaust .648"
Timing at .050 Lift: Open	Close	
Intake	14.5° BTDC	62.5° ABDC
Exhaust	53.5° BBDC	13.5° ATDC
Centerlines:	Int. 109.5° ATDC	Exh. 114.5° BTDC
Lobe Separation:	112°	

CAUTION: Use Edelbrock Performer-Link Timing Chain and Gear Set #7810 or Accu-Drive gear drive #7891. Do not use late model timing chain and gear sets that are designed for emission-controlled engines. These timing sets are machined in a retarded position and are not recommended for this camshaft installation. Edelbrock Timing Sets feature three keyways for specified timing selection. Use "0" position for most applications.

Catalog #2263, 2264
Rev. 5/15/13 - QT/mc

©2013 Edelbrock LLC
Brochure #63-2263C

**CAMSHAFT: Performer RPM Roller Hydraulic
CATALOG #2263 & 2264**



**ENGINE: 1967 & Later Chevrolet 500+ c.i.d. V8
RPM RANGE: 1500-6500**

CAUTION: Do not use dual valve springs. Use recommended valve springs with closed pressure of 175 lbs., open pressure of 465 lbs, and max lift of .700". Use stock ratio rockers only.

Duration at .006" Lift:	Intake 308°	Exhaust 315°
Duration at .050" Lift:	Intake 248°	Exhaust 256°
Lift at cam:	Intake .371"	Exhaust .381"
Lift at valve:	Intake .632"	Exhaust .648"
Timing at .050 Lift: Open	Close	
Intake	14.5° BTDC	62.5° ABDC
Exhaust	53.5° BBDC	13.5° ATDC
Centerlines:	Int. 109.5° ATDC	Exh. 114.5° BTDC
Lobe Separation:	112°	

CAUTION: Use Edelbrock Performer-Link Timing Chain and Gear Set #7810 or Accu-Drive gear drive #7891. Do not use late model timing chain and gear sets that are designed for emission-controlled engines. These timing sets are machined in a retarded position and are not recommended for this camshaft installation. Edelbrock Timing Sets feature three keyways for specified timing selection. Use "0" position for most applications.

Catalog #2263, 2264
Rev. 5/15/13 - QT/mc

©2013 Edelbrock LLC
Brochure #63-2263C

**CAMSHAFT: Performer RPM Roller Hydraulic
CATALOG #2263 & 2264**



**ENGINE: 1967 & Later Chevrolet 500+ c.i.d. V8
RPM RANGE: 1500-6500**

CAUTION: Do not use dual valve springs. Use recommended valve springs with closed pressure of 175 lbs., open pressure of 465 lbs, and max lift of .700". Use stock ratio rockers only.

Duration at .006" Lift:	Intake 308°	Exhaust 315°
Duration at .050" Lift:	Intake 248°	Exhaust 256°
Lift at cam:	Intake .371"	Exhaust .381"
Lift at valve:	Intake .632"	Exhaust .648"
Timing at .050 Lift: Open	Close	
Intake	14.5° BTDC	62.5° ABDC
Exhaust	53.5° BBDC	13.5° ATDC
Centerlines:	Int. 109.5° ATDC	Exh. 114.5° BTDC
Lobe Separation:	112°	

CAUTION: Use Edelbrock Performer-Link Timing Chain and Gear Set #7810 or Accu-Drive gear drive #7891. Do not use late model timing chain and gear sets that are designed for emission-controlled engines. These timing sets are machined in a retarded position and are not recommended for this camshaft installation. Edelbrock Timing Sets feature three keyways for specified timing selection. Use "0" position for most applications.

Catalog #2263, 2264
Rev. 5/15/13 - QT/mc

©2013 Edelbrock LLC
Brochure #63-2263C