



STAGE II TRUCK CAM GEN 3 & GEN 4 LS APPLICATIONS

<i>INTAKE DURATION @ .006"</i>	<i>262°</i>	<i>INTAKE CENTERLINE</i>	<i>111°</i>
<i>EXHAUST DURATION @ .006"</i>	<i>268°</i>	<i>EXHAUST CENTERLINE</i>	<i>111°</i>
<i>INTAKE DURATION @ .050"</i>	<i>212°</i>	<i>LOBE SEPARATION ANGLE</i>	<i>111°</i>
<i>EXHAUST DURATION @ .050"</i>	<i>218°</i>	<i>A - EVO @ .050"</i>	<i>40° BBDC</i>
<i>LOBE LIFT INTAKE</i>	<i>.325"</i>	<i>B - EVC @ .050"</i>	<i>-2° ATDC</i>
<i>LOBE LIFT EXHAUST</i>	<i>.325"</i>	<i>C - IVO @ .050"</i>	<i>-5° BTDC</i>
<i>ROCKER RATIO</i>	<i>1.7</i>	<i>D - IVC @ .050"</i>	<i>37° ABDC</i>
<i>NET LIFT INTAKE</i>	<i>.553"</i>	<i>LASH</i>	<i>N/A</i>
<i>NET LIFT EXHAUST</i>	<i>.553"</i>	<i>BTR31218110</i>	