

Rear Lift Bar Set-Up - Weld-In
Item #3020



Box Contents:

- (2) 3020 Rear Control Arm
- (2) 3010 Driver Plate
- (2) 3010 Passenger Plate
- (8) 2142 Polyurethane Bushing (Mounted)
- (4) 3016C Steel Sleeve (Mounted)
- (2) 3/4" Steel Sleeve (Loose)
- (4) Grease Fitting
- (1) Hardware Kit (Includes Following)
 - (4) M12 x 100mm Hex Bolt
 - (4) M12 Lock Nut
 - (4) M12 Flat Washer
 - (2) 7/16" x 4" Hex Bolt
 - (2) 7/16" Flat Washer
 - (2) 7/16" Conical Nut

Applications:

* 1978 – 1988 GM G-Body

****NOTE:** (1) 3010 Driver Plate + (1) 3010 Passenger Plate = (1) 3010 Relocation Bracket**

****NOTE:** Grand National 8.5" Rear ends: May require grinding of the factory bracket for the relocation brackets to fit properly due to slight factory variations***

Thank you for Putting Your Trust in A UMI Performance Product!

www.umiperformance.com

1. Block the front wheels and jack the vehicle up to a good working height. Position jack stands under the vehicle frame to allow the rear end to hang freely. Make sure vehicle is stable on jack stands.
2. Remove rear sway bar, if equipped.
3. **ONLY INSTALL ONE SIDE AT A TIME.** Begin with driver's side by removing the rear tire and unbolting the lower control arm (LCA) from its rear mounting point. Use a jack under the yoke to ease bolt removal. Let the LCA swing down. Now remove from frame location.
4. Carefully position the relocation bracket onto the rear axle and position the supplied 7/16" bolt with the 3/4" sleeve into the factory location. Do **NOT** tighten at this time.
****NOTE:** The bottom machined surface of the relocation brackets **MUST** be parallel with the pinion.**
5. To achieve this critical angle symmetry, place a magnetic angle finder on rear end yoke, record this angle, then place the angle finder on the machined bottom surface and pivot the relocation plate until the angle matches the angle measurement from the rear end yoke. (SEE IMAGE #1 & #2)
EXAMPLE: If yoke is facing downward 2 degrees, you must pivot the relocation plate so the machined bottom surface of the plate is also facing downward 2 degrees.
****NOTE:** (1) 3010 Driver Plate + (1) 3010 Passenger Plate = (1) 3010 Relocation Bracket**
(Backing Plates face each other, inward)
6. Once parallel with the pinion, tack weld on (2) exterior edges of the Plate to hold it parallel with the pinion. Repeat this step for the opposite 3010 Plate.
7. Torque the 7/16" bolt to 70 ft-lbs.
8. Weld fully on the outside of the relocation bracket to the rear axle.
9. Let cool, and then install new LCA in frame side first, with grease fitting holes down & offset sway bar holes toward rear end.
10. Using the supplied M12 x 100mm bolt, attach LCA to relocation bracket in any dropped location. Do **NOT** tighten at this time.
NOTE: The 7/16" bolt may need to be loosened so that the LCA can swing up into the bracket.
11. Repeat steps 3-10 on passenger side.
12. Re-install sway bar to new LCA.
13. Load the suspension and torque new M12 bolts to 90 ft-lbs.

Thank you for Putting Your Trust in A UMI Performance Product!

www.umiperformance.com



IMAGE #1: (Measure & Record Yoke Angle)



IMAGE #2: (Match Bracket Angle To Yoke Angle)

Thank you for Putting Your Trust in A UMI Performance Product!
www.umiperformance.com



509 Hemlock St
Philipsburg, PA 16866
Ph- 814.343.6315 Fax- 814.343.6318
Installation Instructions
support@umiperformance.com
www.umiperformance.com

Item # 3020

Rear Lift Bar Set-Up – Weld-In
1978 – 1988 GM G-Body

UMI Performance Inc.
Made in Pennsylvania, USA

Thank you for Putting Your Trust in A UMI Performance Product!
www.umiperformance.com