

65-70 GM B-Body Tubular Non-Adjustable Panhard Bar

Item # 3658



1. Securely block the front wheels of the vehicle. Jack up rear of vehicle to a good working height, make sure both rear wheels are off the ground. Place (2) jack stands under the frame. **Do not Support by rear axle.**
2. Loosen and remove both panhard bar bolts and remove panhard bar from the vehicle, rear end will shift. Save Bolts and nuts if reusing.
Note: On axle side the bolt is permanently attached to the rear end as a stud, this stud must be reused. During removal do not cut, strip or damage this stud. If you purchased a new hardware kit from UMI Performance it supplies a new nut for this stud only and not a new stud.
3. Use the supplied grease tube to lube the outside bushing surfaces of the new panhard bar before install, this will help ease panhard bar into place.
4. Install panhard bar into place starting at the axle stud and with the grease fittings angled towards the ground. Installation will require a partner to put light pressure pushing in on the driver's side tire to line panhard bar holes up correctly, with the panhard bar removed the rear end will shift. A jack placed under the rear-end housing and using up and down movements may also help installation. Use OEM hardware from step 2 to reinstall panhard bar. **Do not** tighten bolts; the vehicle weight must on the rear axle before tightening to prevent bushing preload and inconsistent vehicle height.
5. Jack up vehicle by rear axle, remove jack stands from frame and place stands under rear axle. Release the jack and let the vehicle weight rest on the jack stands.
6. Tighten panhard bar mounting bolts and lube each grease fitting with 1-1 ½ pumps of grease only.

Greasing Your Panhard Bar- Use only Non-Lithium Based Grease, Lithium based grease can wash out with water. Grease your control arm bushings 2-3 times a year adding only 1 pump of grease, **DO NOT OVER GREASE.**

Thank you for putting your trust in a UMI Performance product!

Page 1 of 2



509 Hemlock St
Philipsburg, PA 16866
Ph- 814.343.6315 Fax- 814.343.6318

Installation Instructions

support@umiperformance.com
www.umiperformance.com

DISCLAIMER OF WARRANTY

THE PURCHASER ACCEPTS ALL RESPONSIBILITY FOR THE FINAL USE OF THE PRODUCTS PURCHASED AND SHALL HOLD UMI PERFORMANCE INCORPORATED AND ITS REPRESENTATIVES HARMLESS IN ANY LEGAL PROCEEDING ARISING FROM THE USE OF SUCH PRODUCTS.

UMI PERFORMANCE INCORPORATED DOES NOT WARRANT, GUARANTEE, OR MAKE ANY REPRESENTATION REGARDING THE USE, OR THE RESULT OF THE USE OF ANY PERFORMANCE PRODUCT MANUFACTURED OR DISTRIBUTED BY UMI PERFORMANCE INCORPORATED. PURCHASER ASSUMES THE ENTIRE RISK AS THE RESULT AND PERFORMANCE OBTAINED FROM THE INSTALLATION AND USE OF SAID PERFORMANCE PRODUCTS. UMI PERFORMANCE INCORPORATED ASSUMES NO RESPONSIBILITY FOR AND HEREBY DISCLAIMS ALL WARRANTIES, ORAL OR WRITTEN, EXPRESS OR IMPLIED INCLUDING WITHOUT LIMITATION, THE WARRANTIES OF MERCHANTABILITY AND OF FITNESS FOR A PARTICULAR PURPOSE.

ALL PARTS ARE WARRANTED TO BE FREE OF DEFECT AT THE TIME OF PURCHASE. WARRANTY IS ONLY EXTENDED TO REPLACEMENT OF PARTS FROM UMI PERFORMANCE INCORPORATED AND DOES NOT COVER LABOR, TOWING OR ANY OTHER DIRECT OR INDIRECT COST. UMI PERFORMANCE INCORPORATED IS NOT RESPONSIBLE FOR ANY CONSEQUENTIAL DAMAGE, EXPENSE OR INJURY ARISING FROM THE USE, MISUSE OR IMPROPER INSTALLATION OF ANY PRODUCT MANUFACTURED AND/OR SOLD BY UMI PERFORMANCE INCORPORATED.

Item # 3658

65-70 GM B-Body Panhard Bar

UMI Performance Inc.
Made in Pennsylvania, USA

Thank you for putting your trust in a UMI Performance product!

Page 2 of 2